

Safety data sheet

TOTAL PETROCHEMICALS POLYETHYLENE HDPE FLUFF

Page : 1/9

Product :
PETH-004

Version (en) nr : 10.2

Revised : 15/09/2010
Supersedes : 06/10/2009WARNING :
FOR STACKING
PALLETS, SEE
SECTION 7

1. Identification of the substance / preparation and of the company / undertaking

Trade name	TOTAL PETROCHEMICALS POLYETHYLENE HDPE FLUFF
SDS number	PETH-004
Name of the product	POLYETHYLENE HDPE FLUFF
Chemical name	high and medium density Polyethylene
CAS number	25213-02-9

MATERIAL USE

for more detailed information, see technical data sheet.

Recommended uses and restrictions

Restricted to professional users

RESPONSIBLE FOR PLACING ON THE MARKET

Trade name of the firm

see below this page.

Email address: Petrochemicals.felr-sds@total.com
(Safety data sheet)**EMERGENCY NUMBER**

Emergency call TOTAL PETROCHEMICALS:

- for English speaking countries: +44 (0) 1235 239 670
- for Europe (in local languages): + 33 1 49 00 00 49
- for Africa and Middle East: + 44 (0) 1235 239 671• for China:
+ 86 10 5100 3039
- for Asia Pacific (Hong-Kong, Singapore, Taiwan, Philippines, India,
Vietnam, Sri Lanka, Japan, Korea, Malaysia, Indonesia, Thailand) :
+ 65 3158 1074

Official advisory body

The UK National Poisons Emergency number is 0870 600 6266
(Outside the UK: +44 870 600 6266)

NB: these services are only available to health professionals

IRL: The National Poisons Information Centre
PO Box 1297, Beaumont Hospital, Beaumont Road
Dublin 9.

Telephone: +353 (01) 837 9966 / +353 (01) 809 2568

2. Hazards identification

Classification & Labelling

EC-GHS

Not classified according to the regulation EC 1272/2008 (EC-GHS) and ATP

67/548/EEC & 1999/45/EC

Not classified according to EEC directives 67/548/EEC (dangerous substances) and 1999/45/EC (dangerous preparations).

Main hazards

none to our knowledge



TOTAL PETROCHEMICALS
a division of NV Petrofina SA
rue de l'Industrie 52 Nijverheidsstraat
B- 1040 BRUSSELS
BELGIUM
phone : +32 (0)2.288.91.11 - fax : +32 (0)2.288.33.69
www.totalpetrochemicals.com

ExESS©©

Safety data sheet

TOTAL PETROCHEMICALS POLYETHYLENE HDPE FLUFF

Product :
PETH-004

Version (en) nr : 10.2

Page : 2/9
Revised : 15/09/2010
Supersedes : 06/10/2009

low risk for temperatures below 130 °C

Adverse human health effects

Inhalation

fine dust may cause irritation of respiratory system and mucous. if heated to more than 130°C, the product may form vapours or fumes which may cause irritation of respiratory tract and cause coughing and sensation of shortness of breath.

Skin contact

in contact with hot material, may cause severe thermal burns

Eye contact

fine dust may cause irritation to ocular mucous.

Ingestion

polyolefins are biologically inert.

Adverse environmental effectsbecause of its structure, the product should not be dangerous for aquatic life
non biodegradable**Adverse physicochemical effects**combustible if exposed to flames.
flowing product can create electrical charge, resulting sparks may ignite dust or cause an explosion in some concentration ranges.**Label elements****EC-GHS**

Not classified according to the regulation EC 1272/2008 (EC-GHS) and ATP

Pictogram(s)

-

WARNING :
FOR STACKING
PALLETS, SEE
SECTION 7**Other hazards**

no information available

3. Composition / information on ingredients**chemical name**

Polyethylene

Chemical formula

(C₂H₄)_x

CAS number

25213-02-9

EINECS or ELINCS number

the product is a polymer, following the European regulation, registration on the EINECS (European Inventory of Existing Commercial Chemical Substances) inventory is not required.

EC-GHS

non required

67/548/EEC & 1999/45/EC

non required

Substances presenting a health hazard

none to our knowledge

Chemical family

Olefinic polymer

Additives

Antioxidants and stabilisers : 3000 ppm maximum

TOTAL PETROCHEMICALS
a division of NV Petrofina SA
rue de l'Industrie 52 Nijverheidsstraat
B- 1040 BRUSSELS
BELGIUM
phone : +32 (0)2.288.91.11 - fax : +32 (0)2.288.33.69
www.totalpetrochemicals.com

ExESS©©

Safety data sheet

TOTAL PETROCHEMICALS POLYETHYLENE HDPE FLUFF

Page : 3/9

Product :
PETH-004

Version (en) nr : 10.2

Revised : 15/09/2010
Supersedes : 06/10/2009

4. First-aid measures

Description of first aid measures

Route of exposure

Inhalation

exposure to spray, fumes and vapours produced by heated or burned product:
bring patient into fresh air
seek medical advice.

Skin contact

exposure to splashing of hot product:
treat the affected part with cold water (by spraying or immersion).
no attempt should be made to detach molten product adhering to the skin or to remove clothing attached with molten material, the injured body part would risk being pulled out; usually the layer detaches itself after a few days.
in case of severe burns, seek hospital treatment

Eye contact

exposure to splashing of hot product:
treat the eyes with cold water.
Seek specialist advice at hospital or medical centre
fine dust may cause irritation to ocular mucous.
in case of irritation caused by fine dust: wash with copious volumes of water, until the irritation disappears.

Ingestion

ingestion during handling is not likely.
remove material from mouth
do not induce vomiting.

Protective equipment for first-aiders

wear suitable breathing equipment, in case of risk of exposure to vapour or fumes.

Most important symptoms and effects

refer to § 11 for more details on effects.

Indication of any medical attention

no information available

5. Fire - fighting measures

Fire-class regulation

A: Solid material fires, principally of organic nature, that burn with incandescence

Technical measures

stop the fire spreading.
call the fire brigade immediately.
evacuate non-essential personnel
protective clothing, goggles and self-contained breathing equipment should be made available for firemen.

Extinguishing media

Suitable

for minor fires : carbon dioxide (CO₂) or powder, water
for more extensive fires : foam, water spray (mist) to cool the surfaces exposed to the fire.

Not to be used

do not use water jets (stick jets) for extinguishing fire since they could


TOTAL PETROCHEMICALS

a division of NV Petrofina SA
rue de l'Industrie 52 Nijverheidsstraat
B- 1040 BRUSSELS
BELGIUM
phone : +32 (0)2.288.91.11 - fax : +32 (0)2.288.33.69
www.totalpetrochemicals.com

ExESS©

Safety data sheet

TOTAL PETROCHEMICALS POLYETHYLENE HDPE FLUFF

Page : 4/9

Product :
PETH-004

Version (en) nr : 10.2

Revised : 15/09/2010
Supersedes : 06/10/2009

Special peril	help to spread the flames complete combustion, with an excess of oxygen forms: carbon dioxide (CO ₂) and water vapour. partial combustion, forms also: carbon monoxide (CO), soot and cracked products: aldehydes, ketones , Acetone , Acetaldehyde , Formaldehyde , Acrolein , hydrocarbons and volatile fatty acids
Protective equipment for firefighters	wear suitable breathing equipment, in case of risk of exposure to vapour or fumes.

6. Accidental release measures

Personal precautions

For non-emergency personnel

wear a suitable anti-dust respirator
where exposure is likely, protective clothing must be worn including gloves
goggles/spectacles

For emergency responders

wear suitable breathing equipment, in case of risk of exposure to vapour or fumes.

After spillage / leakage

on soil

granules spilled on the floor can cause a risk of slipping on smooth surfaces.
recover the spilled product by sweeping or suction; put it in containers to facilitate its disposal.
dispose safely in accordance with local or national regulations.

on water

prevent the spilled material from spreading.
if the material has been discharged into a stream or a sewerage system, inform the authorities of the possible presence of floating materials.
clean up the water surface by creaming off debris from the top.
refer to a specialist for waste disposal in a safe manner in accordance with local or national regulations.

refer to points 8 and 13

7. Handling and storage

Important

refer to any national measures that may be relevant.

HANDLING

Technical measures

all pneumatic transport equipment must be electrically earthed.
avoid dust accumulation by use of filters in the pneumatic transport equipment.

STOCKAGE

Storage conditions

store at ambient temperature and at atmospheric pressure in original packaging (plastic or cardboard boxes) or in silo made of appropriate material (aluminium, stainless steel, ...).



TOTAL PETROCHEMICALS

a division of NV Petrofina SA
rue de l'Industrie 52 Nijverheidsstraat
B- 1040 BRUSSELS
BELGIUM
phone : +32 (0)2.288.91.11 - fax : +32 (0)2.288.33.69
www.totalpetrochemicals.com

ExESS®©

Safety data sheet

TOTAL PETROCHEMICALS POLYETHYLENE HDPE FLUFF

Page : 5/9

Product :
PETH-004

Version (en) nr : 10.2

Revised : 15/09/2010
Supersedes : 06/10/2009

Storage of pallets	do not store near highly flammable materials. store away from heating source. avoid static electricity build up with connection to earth. store in dry, well-ventilated area. prolonged storage preferably out of the sun or other sources of radiation
Storage of pallets	two pallets may be stacked on flooring in sound condition. however, when the pictorial warning as shown on the top of the safety data sheet is affixed to the pallet, the pallet must never be placed either on top of or below another pallet. N.B. :here the term pallet includes both the pallet and its load. when pallets are stored in racks, it should be checked whether the pallet is fit for stacking in the concerned racks
container	
Suitable	Polyethylene,paper bags,stainless steel
SPECIFIC USE(S)	no information available
refer to point 8	

8. Exposure controls / personal protection

Exposure controls

refer to any national measures that may be relevant.

OCCUPATIONAL EXPOSURE LIMIT

inhalable dust particles:
US (ACGIH-2009): TLV-8h TWA: 10 mg/m³
UK: HSE EH40/2005:
Long-term exposure limit (8-hour TWA reference period) : 10 mg/m³ (Total Inhalable Dust)
IRL(2002): OEL (8h): 10 mg/m³ (total inhalable)
ZA (2006): OEL (8h): 10 mg/m³ (inhalable particulate: PNOC)
respirable dust particles:
US (ACGIH-2009): TLV- 8h TWA: 3 mg/m³
UK: HSE EH40/2005:
Long-term exposure limit (8-hour TWA reference period) : 4 mg/m³ (Respirable Dust)
IRL(2002): OEL (8h): 4 mg/m³ (respirable)
ZA (2006): OEL (8h): 5 mg/m³ (respirable particulate: PNOC)

EXPOSURE CONTROLS

Occupational exposure controls

Personal protection



Respiratory protection

in case of risk of overexposure to dust, vapour or fumes (during product processing), it is recommended that a local exhaust system is placed above the conversion equipment (a fume hood) and the working area must be properly ventilated.



TOTAL PETROCHEMICALS
a division of NV Petrofina SA
rue de l'Industrie 52 Nijverheidsstraat
B- 1040 BRUSSELS
BELGIUM
phone : +32 (0)2.288.91.11 - fax : +32 (0)2.288.33.69
www.totalpetrochemicals.com

ExESS©©

Safety data sheet

TOTAL PETROCHEMICALS POLYETHYLENE HDPE FLUFF

Page : 6/9

Product :
PETH-004

Version (en) nr : 10.2

Revised : 15/09/2010
Supersedes : 06/10/2009

	wear a suitable anti-dust respirator recommended filter type : P1
Skin and body protection	where exposure is likely, protective clothing must be worn including gloves
Eye protection	goggles/spectacles
Other personal protection	safety non-slip shoes in areas where spills or leaks can occur.
Environmental exposure controls	no information available

9. Physical and chemical properties

GENERAL INFORMATION

Appearance	powder (fluff 600 µm > X < 1000 µm)
Physical state at 20°C	solid
Colour	white opaque
Odour	odourless

IMPORTANT HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Change in physical state at 1013 hPa

Melting range (°C)	90 to 160
Flash point (ASTM D 93) (°C)	± 320
Auto-ignition temperature (°C)	> 350
Explosion limits (kg/m ³)	:
Lower	0,015 (for polymer dust < 63 µm)
Min. ignition energy at 20°C (mJ)	63
Vapour pressure at 20°C (hPa)	none
Density, mass at 20°C (kg/m ³)	945 - 960 (ISO 1183)
Solubility in water at 20°C (mg/l)	insoluble
pH value (concentrated product)	not applicable
Viscosity (mm ² /s)	not applicable

OTHER INFORMATION

no information available

10. Stability and reactivity

REACTIVITY

Stability	stable under normal operating conditions of storage, handling and use
Hazardous reactions	dust may form an explosive mixture with air, ignited by sparks or sources of ignition.

CONDITIONS TO AVOID

avoid contact with strong oxidizing materials and fluorine



TOTAL PETROCHEMICALS

a division of NV Petrofina SA
rue de l'Industrie 52 Nijverheidsstraat
B- 1040 BRUSSELS
BELGIUM

phone : +32 (0)2.288.91.11 - fax : +32 (0)2.288.33.69
www.totalpetrochemicals.com

ExESS©©

Safety data sheet

TOTAL PETROCHEMICALS POLYETHYLENE HDPE FLUFF

Page : 7/9

Product :
PETH-004

Version (en) nr : 10.2

Revised : 15/09/2010
Supersedes : 06/10/2009**HAZARDOUS DECOMPOSITION PRODUCTS**avoid proximity or contact with flames or sparks
it is recommended not to heat at a temperature higher than 320 °Ccomplete combustion, with an excess of oxygen forms: carbon dioxide (CO₂) and water vapour.
partial combustion, forms also: carbon monoxide (CO), soot and cracked products: aldehydes, ketones

Advice to prevent explosion

avoid dust accumulation by use of filters in the pneumatic transport equipment.
thoroughly ventilate the working place.
all conductive materials must be electrically earthed.
in case of pneumatic alimentation, feed the extruders by aspiration, use preferably nitrogen as carrier gas**11. Toxicological information****ACUTE TOXICITY**

polyolefins are biologically inert.

Ingestion

because of its composition, the product should be considered as practically not harmful

LOCAL EFFECT

Inhalation

dust may cause irritation of respiratory system.
if heated to more than 130°C, the product may form vapours or fumes which may cause irritation of respiratory tract and cause coughing and sensation of shortness of breath.

Skin contact

because of its composition, the product should be considered practically as not irritating
in contact with hot material, may cause severe thermal burns
thermal decomposition products are produced at elevated temperatures and these may be irritating

Eye contact

because of its composition, the product should be considered practically as not irritating
fine dust may cause irritation to ocular mucous.
splashing of molten droplets causes ocular tissue burns.
thermal decomposition products are produced at elevated temperatures and these may be irritating**SPECIFIC EFFECTS**polyolefins are biologically inert.
no particular preoccupation for man
(Genotoxicity, carcinogenicity, reproductive toxicity)**12. Ecological information**

Information on ecological effects

avoid losses to the environment whenever possible.

ECOTOXICITY

because of its structure, the product should not be dangerous for aquatic life

PERSISTENCE AND DEGRADABILITY

persistent in the environment

Biodegradation

this substance is slowly biodegradable

**TOTAL PETROCHEMICALS**

a division of NV Petrofina SA
 rue de l'Industrie 52 Nijverheidsstraat
 B- 1040 BRUSSELS
 BELGIUM
 phone : +32 (0)2.288.91.11 - fax : +32 (0)2.288.33.69
 www.totalpetrochemicals.com

ExESS©

Safety data sheet

TOTAL PETROCHEMICALS POLYETHYLENE HDPE FLUFF

Page : 8/9

Product :
PETH-004

Version (en) nr : 10.2

Revised : 15/09/2010
Supersedes : 06/10/2009

BOD 5 (gO2/g)	below the detection limit
BIOACCUMULATIVE POTENTIAL	potential bioaccumulation of the product in environment is very low
MOBILITY	
water / air	there is a slow loss by evaporation volatile organic compound (VOC) content of this product is < at 1 % weight
soil and sediments	because of its physico-chemical properties, the product has a low soil mobility
water	the product, in cases of accidental discharge, floats on the surface, is insoluble and its evaporation into air is practically nil
Results of PBT and vPvB assessment	non required

13. Disposal considerations

Waste disposal	according to local regulations. authorized disposal as refuse for reprocessing do not dispose off by means of sinks, drains or into the immediate environment may be used as fuel in suitably designed installations. incinerate with household refuse in a municipal solid waste incinerator plan.
Industrial waste number EC	07 02 13, 16 01 19, 17 02 03 & 20 01 39: plastics
API (Association of Plastic Industry) Code	2 : HDPE: high density Polyethylene

14. Transport information

Road (ADR) / Rail (RID)	Not restricted for transport.
UN Number	not applicable
Marine (IMO)	Not restricted for transport.
Air transport (ICAO / IATA)	Not restricted for transport.

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Germany

Wassergefährdungsklasse NWG: non-hazardous to waters

Registration

These registration entries are for polymers only. For additives, please refer to TOTAL PETROCHEMICALS who will provide the necessary certification



TOTAL PETROCHEMICALS

a division of NV Petrofina SA
rue de l'Industrie 52 Nijverheidsstraat
B- 1040 BRUSSELS
BELGIUM

phone : +32 (0)2.288.91.11 - fax : +32 (0)2.288.33.69
www.totalpetrochemicals.com

ExESS©©

Safety data sheet

TOTAL PETROCHEMICALS POLYETHYLENE HDPE FLUFF

Page : 9/9

Product :
PETH-004

Version (en) nr : 10.2

Revised : 15/09/2010
Supersedes : 06/10/2009

the product is a polymer, following the European regulation, registration on the EINECS (European Inventory of Existing Commercial Chemical Substances) inventory is not required.
listed on the United States TSCA (Toxic Substances Control Act) inventory
listed on the Canadian DSL (Domestic Substances List) inventory.
listed on the Japanese ENCS (Existing & New Chemical Substances) inventory.
listed on the AICS (the Australian Inventory of Chemical Substances).
listed on the Korean ECL (Existing Chemical List) inventory.
listed on the Filipino PICCS (Philippine Inventory of Chemicals and Chemical Substances) inventory.
listed on the swiss (liste des toxiques IGS/ IGS Giftliste 2003-2004) inventory
listed on the People's Republic of China register: CRC-SEPA (Chemical Registration Center for Chinese State Environmental Protection Administration)

16. Other information

Training advice

The use of this product requires specific training.
The user must receive all product information in order to handle the product safely
(personal protection equipment and best practice standards)

Further information

no information available

Safety data sheet conforms to the Regulation (EU) N° 1907/2006

This information applies to the PRODUCT AS SUCH and conforming to specifications of TOTAL PETROCHEMICALS.

In case of formulations or mixtures, it is necessary to ascertain that a new danger will not appear.

The information contained is based on our knowledge of the product, at the date of publishing and it is given quite sincerely. However the revision of some data is in progress.

Users are advised of possible additional hazards when the product is used in applications for which it was not intended. This sheet shall only be used and reproduced for prevention and security purposes.

The references to legislative, regulatory and codes of practice documents cannot be considered as exhaustive.

It is the responsibility of the person receiving the product to refer to the totality of the official documents concerning the use, the possession and the handling of the product.

It is also the responsibility of the handlers of the product to pass on to any subsequent persons who will come into contact with the product. (usage, storage, cleaning of containers, other processes) the totality of the information contained within this safety data sheet and necessary for safety at work, the protection of health and the protection of environment.

The (*) indicate the changes made with respect to the previous version.



TOTAL PETROCHEMICALS

a division of NV Petrofina SA
rue de l'Industrie 52 Nijverheidsstraat
B- 1040 BRUSSELS
BELGIUM
phone : +32 (0)2.288.91.11 - fax : +32 (0)2.288.33.69
www.totalpetrochemicals.com

ExESS©©